

The Kährs logo consists of the word "Kährs" in a white, bold, sans-serif font, with a registered trademark symbol (®) to its upper right. It is set against a solid red square background.

Matt Lacquer

Kährs Matt Lacquer is a 2-component water-based polyurethane finish for wood and parquet floors. Suitable for re-lacquering of matt lacquered Kährs floors. Apply with roller, brush or applicator. The finish has excellent durability and is highly resistant to mechanical wear and commonly used household cleaners and detergents. Kährs Matt Lacquer is suitable for residential and commercial use.

Application

The surface to be finished must be carefully sanded and free of dust, dirt and other foreign materials. Depending on the level of wear on the old surface, this could be done either by relacquering or by sanding down the surface. The temperature of the floor should not be below 14°C nor exceed 28°C. Ideal is a 20°C floor temperature and a relative humidity of 55%.

Add the hardener to the Lacquer and mix thoroughly before use. Open and allow time for air to vaporize prior to application (10 minutes). To be used within 4 hours. Always test the finish on a smaller area to ensure colour and adhesion.

1. Relacquering: Clean the surface using Kährs Remover and then wash the floor with clean water with a slightly damp cloth. Use a little water as possible. Recommended application: 1 coat, coverage 0,1 l/m²
2. Sanding down: Recommended application: 2-3 coats. Buff/screed the floors after first coat. Minimum recommended thickness for coverage is 0,25 l/m², total amount. Be very careful when using the surface during the first four weeks.



ARTICLE NUMBER: 710618

TECHNICAL DATA

Bonding agent: Polyurethane
Viscosity: 21-22 s (FC 4, 20°C)
Solids by volume: 32%
Approx. weight: 1,1 kg/l
Coverage: Approx. 8-10 m²/l per coat
Drying time On bare floors: 30-60 minutes
Succeeding coats: 2-4 hours
Curing time, approx.: 5 days
pH: Approx. 8-9
Shelf life: 12 months in unopened container. Do not store below 15°C
Resistance to Chemicals: Resistant to water and regular household cleaners and detergents. Does not withstand recurring use of heavier chemicals.
Frost tolerance: May be subjected to frost
Friction: 0,4-0,65 (DIN standards no 18032, part 2)
Clean-up: Use water to clean tools before finish has hardened.
Toxicity: See Material Safety Data Sheet
Flammability: Non-flammable
Packaging: 1 l (0,9 + 0,1)



Matt Lacquer

Care and Maintenance

You can walk on the floor 8 hours after the last coat. The surface can hold lighter pieces of furniture after 24 hours. Heavier items as well as rugs need await curing, at least for four days. Regular care involves vacuuming or slightly damp mopping using Kährs Cleaner or Spray Cleaner, see separate information for these products. Allow at least 3 weeks before using strong alkaline cleaning products.

Health and Environment

Kährs Lacquer is not classified as hazardous to your health or the environment. The hardener as separate component is classified as irritant. Usual precautions for handling chemical products should be observed. Ensure adequate ventilation. Use protective goggles and gloves. In case of skin contact, wash thoroughly with soap and water. For eyes, flush plenty water. For further information, please see the Material Safety Data Sheet.



ARTICLE NUMBER: 710618

TECHNICAL DATA

Bonding agent: Polyurethane
Viscosity: 21-22 s (FC 4, 20°C)
Solids by volume: 32%
Approx. weight: 1,1 kg/l
Coverage: Approx. 8-10 m²/l per coat
Drying time On bare floors: 30-60 minutes
Succeeding coats: 2-4 hours
Curing time, approx.: 5 days
pH: Approx. 8-9
Shelf life: 12 months in unopened container. Do not store below 15°C
Resistance to Chemicals: Resistant to water and regular household cleaners and detergents. Does not withstand recurring use of heavier chemicals.
Frost tolerance: May be subjected to frost
Friction:: 0,4-0,65 (DIN standards no 18032, part 2)
Clean-up: Use water to clean tools before finish has hardened.
Toxicity: See Material Safety Data Sheet
Flammability: Non-flammable
Packaging: 1 l (0,9 + 0,1)