



SATIN OIL-TINTED *CONSUMER VERSION* MAINTENANCE OIL

Kährs Satin Oil is a hardening urethane oil for maintaining wood and parquet floors. Satin Oil gives the floor a protective oil layer with a beautiful shine. Satin Oil protects by penetrating the floor surface.

AFTER INSTALLATION

Use clear Satin Oil, art.nr.710553. See Product Data Sheet Satin Oil-Clear.

MAINTENANCE ON DEMAND

Use clear Satin Oil, art.nr.710553. See Product Data Sheet Satin Oil-Clear.

RENOVATION OF STAINED FLOORS

After extended use, it may be necessary to renovate the surface treatment and replace it with a new **Tinted Satin Oil** treatment.

1. Apply Kährs Cleaner evenly over the surface.
2. Clean the surface using Kährs micro mop. Scrub until the dirt has been dissolved. For very dirty floors replace the micro mop using a rough brush.
3. Remove cleaner and dirt using a wrung out cloth.
4. Dry the surface using a dry cloth and leave the floor to dry for 30 minutes.

For very dirty floors or on floors with heavy textures, it might be necessary to repeat step 1, step 2, and step 3.

5. Apply Kährs Stained Satin Oil on the surface. Use Kährs Micro Mop and spread the oil evenly. This is done by scrubbing along and across the floor board until a very thin and even oil layer is reached.
6. Let the surface rest for 10-15 minutes.



ARTICLE NUMBER:

710585, Dark-Brown 01	(matching for example Romanov)
710586, Dark-Grey 01	(matching for example Ulf)
710587, Grey-Brown 01	(matching for example Sture)
710588, White 01	(matching for example Olof)
710589, White 02	(matching for example Gustaf)

TECHNICAL DATA

Bonding agent: Urethane modified alkyd resin

Solvent: N-Paraffins

Solids by weight: Approx. 22%

Application temperature: 14-28 °C

Shelf life: 24 months in unopened container. Do not expose to temperatures exceeding 40° C

Frost tolerance: Yes

Clean-up: Use mineral spirits to clean tools before oil has hardened

Toxicity: Not classified

Flammability: Not classified

Packaging: 1 liter can

Note! A danger of self-ignition exists in contact with organic materials (e.g. cotton cloths, saw dust, absorbing insulation materials etc.) due to self-drying oil content. Rags and other organic materials soaked in oil have to be put into water immediately after use, in order to avoid self-ignition.



If a stronger recolouring is needed, repeat step 5 and step 6. This can be done maximum 3 times, since too thick layers will result in a sticky surface.

Polish the surface using a new dry Micro Mop. This is done to secure that the oil has been evenly spread.

Please observe that two layers of thin oil gives a better result than 1 thick layer of oil. Applying a high amount of oil will result in a sticky surface.

Recommended dosage

100 ml (1 dl) of Kährs Satin Oil per 30m²

Drying Time

After a drying time of 5 hours the floor can be used with care, but needs 12 hours before lighter furniture can be moved back. Wait 24 hours to move back carpets and heavier furniture.

Health and Environment

Kährs Satin Oil contains N-Paraffins. Inhaling or frequent exposure may be hazardous. Avoid inhaling fumes. Usual precautions for handling chemical products should be observed. Ensure adequate ventilation. Use protective goggles and gloves. In case of ingestion, immediately seek medical advice and refer to container and label. For further information, please see the Material Safety Data Sheet.



ARTICLE NUMBER:

710585, Dark-Brown 01	(matching for example Romanov)
710586, Dark-Grey 01	(matching for example Ulf)
710587, Grey-Brown 01	(matching for example Sture)
710588, White 01	(matching for example Olof)
710589, White 02	(matching for example Gustaf)

TECHNICAL DATA

Bonding agent: Urethane modified alkyd resin

Solvent: N-Paraffins

Solids by weight: Approx. 22%

Application temperature: 14-28 °C

Shelf life: 24 months in unopened container. Do not expose to temperatures exceeding 40° C

Frost tolerance: Yes

Clean-up: Use mineral spirits to clean tools before oil has hardened

Toxicity: Not classified

Flammability: Not classified

Packaging: 1 liter can

Note! A danger of self-ignition exists in contact with organic materials (e.g. cotton cloths, saw dust, absorbing insulation materials etc.) due to self-drying oil content. Rags and other organic materials soaked in oil have to be put into water immediately after use, in order to avoid self-ignition.